

PUDLO Membrane Granules

PUDLO Membrane Granules - a granular sodium bentonite which is used as an ancillary product for sealing the PUDLO BW Membrane

USES

PUDLO Membrane Granules is used for the detailing work on:

- Sealing of service penetrations through the PUDLO BW Membrane

APPLICATION & INSTALLATION

Refer to PUDLO BW Membrane installation manual

SURFACE PREPARATION

- Surface should be free from dirt, debris and loose particles
- PUDLO Membrane Granules should not be applied on standing water

PRODUCT DIMENSIONS, COVERAGE & PACKAGING

- 20kg bag

FURTHER INFORMATION

For more accessories used with PUDLO Membrane Granules, please contact: technical@pudlo.com



BENEFITS

- Easy to mix and quick to install
- Fills cavities between the service penetration and BW Membrane

HEALTH & SAFETY

Product should be used with adequate ventilation and dust should not be breathed in.

All workers using this product should wear the correct PPE and approved breathing apparatus.

Avoid skin and eye contact and do not ingest.

Refer to PUDLO Membrane Granules MSDS for all other safety information.

PHYSICAL & CHEMICAL PROPERTIES AND HAZARDS

For chemical properties, please refer to PUDLO Membrane Granules MSDS

ANCILLARIES

TECHNICAL DATA

Application	Rate
Wall / Footing Fillet – 38mm	8.0 l/m (approx.) dry granules 2.0 l/m (approx.) granules mixed with water form a paste
Rood Desk Layer – 3mm	70 sq ft (6.5 sq m)

SUPPORTING DOCUMENTS

- PUDLO Membrane Granules MSDS
- PUDLO Membrane Granules Installation Manual
- Product webpage - please see www.pudlo.com

PRODUCT NUMBER

4750/0015