

ANCILLARIES

PUDLO Membrane Seal

PUDLO Membrane Seal is a sodium bentonite, butyl-rubber based mastic

USES

PUDLO Membrane Seal is used for the detailing work on:

- Fillets at horizontal and vertical inside corners
- Flashing material around drains, mechanical and electrical penetrations
- Sealing material at waterproofing terminations below ground
- Repairs to small concrete surface defects prior to placing PUDLO Membrane Seal

APPLICATION & INSTALLATION

- Surface should be free from dirt, debris, dust, grease, rust, oil, curing agents, other contaminants and loose particles
- PUDLO Membrane Seal should not be applied on standing water
- A fine hair broom provides the best adhesion and minimises waste
- Product should only be applied prior to, or just after, the waterproofing membrane is in position, to avoid being exposed for prolonged periods prior to placement of concrete
- Fillets around service penetrations should be continuous and a minimum of 19mm thick. PS Membrane Seal must extend 38mm at 5mm thickness onto the penetration. Where hydrostatic pressure is of 10m or greater, double the application rates
- Membrane seal can be applied where both ambient and surface temperatures are -4°C or above



BENEFITS

- Easy to apply
- Bonds to most substrate materials

NOTE: PUDLO Membrane Seal is not an expansion joint sealant

ANCILLARY PRODUCTS

- PUDLO BW Membrane

STORAGE & SHELF LIFE

Store above 4°C before application

PRODUCT DIMENSIONS, COVERAGE & PACKAGING

- 15kg tub

HEALTH & SAFETY

Please refer to PUDLO Membrane Seal MSDS for all other safety information

PHYSICAL & CHEMICAL PROPERTIES AND HAZARDS

For chemical properties, please refer to PUDLO Membrane Seal MSDS

FURTHER INFORMATION

For further information on accessories that are used with PUDLO Membrane Seal, please contact: technical@dbgholdings.com.

ANCILLARIES

TECHNICAL DATA**APPROXIMATE COVER RATE GUIDE**

Usage	Typical coverage
19mm inside corner fillet	1.6 lnm / kg
2.3mm thick flashing fillet	0.3 sq m / kg
19mm inside corner fillet with 150mm, 2.3mm thick extensions	0.6 lnm / kg
2.3mm by 100mm wide termination lap fillet	3.0 lnm / kg

SUPPORTING DOCUMENTS

- PUDLO Membrane Seal MSDS
- PUDLO Membrane Seal Installation Manual
- Product webpage - please see www.pudlo.com

PRODUCT NUMBER**4750/0016**